



Softgel Tumble Dryer



TD8

Softgel Tumble Dryer

TD8

Features

- Anodized aluminum frame and stainless steel covers with number 4 finish for fast, thorough cleaning.
- Variable basket speeds (up to 80 rpm), completely adjusted through the operator's panel
- Maximum basket load - 12 kg.
- High capacity frequency drive blower unit.
- Built in heating allows for gentle heating of specific products.
- Light-weight baskets with stainless steel perforated plate allow for quick changeovers, easy clean-up and inspection.
- Lightweight, simple to install, clear Lexan covers.
- Lighted motor housing service area.
- Quick change filter access doors.
- Easy lubrication from the side of the machine.
- Smooth surface in all areas for complete cleaning.


Mechanism

- PLC is incorporated within the stand alone unit
- One variable speed direct drive electrical motor rotates the baskets
- Programmable drying and capsule transfer time
- Pneumatic actuated doors allow capsules to be transferred throughout the tumbler and be discharged at the end of the drying cycle

Softgel Tumble Dryer

TD8

Specification



TD8	
Dimensions (mm)	3526 W X 1387 D X 1377 H
Weight (kg)	
TD Electrical Power	12 KVA without heaters
Compressed Air	8 Bar

TECHNOPHAR

Technophar Global Headquarters
3293 St. Etienne Blvd.
Windsor, Ontario, Canada N8W 5B1
Phone: +1 519-946-0800
www.technophar.com