

# technophar

BY ROQUETTE

## Capsule Band-Sealing Machine

### S2 MODEL



- ✓ PORTABLE
- ✓ PREVENTS COUNTERFEIT PRODUCTS
- ✓ IMPROVES SHELF-LIFE & PRODUCT DURABILITY
- ✓ MEETS cGMP STANDARDS
- ✓ DIFFERENTIATE YOUR PRODUCT'S BRAND



# Capsule Band-Sealing Machines

## *S2 Model*

The **S-2 Model** utilizes the capsule banding process, with commercially proven technology, to securely seal the body and cap of two-piece hard-shell capsules. Sealing bands contribute to a more durable, shelf-stable product and help to differentiate your product's brand. The banding process is approved by the FDA for pharmaceutical products, including prescription and OTC products, and has been used throughout the nutraceutical industry.

## Features

- Single Unit Portable Capsule Sealing-Band Machine.
- Prevents the leakage of liquid fills.
- Reduces oxidation of the capsule contents.
- Demonstrates tamper-resistance to prevent counterfeit products.
- Newly designed top plate makes it easy to work inside the machine.
- Easy to clean top-plate and chain assembly by lifting the machine's lid.
- Exterior sensors replaced with smaller interior sensors.
- New in-line plate positioning creates a higher capacity with better and faster sealing.
- Newly simplified control panel.

# Capsule Band-Sealing Machines

## *S2 Model*

## Mechanism

### The S2 Model consists of:

#### EMERGENCY STOP Switch

- This two-position switch controls the motor's power and heater.

#### RUN Switch

- Starts the capsule slat drive motor.

#### ON-OFF Switch, Heater/Banding Wheel

- Starts and stops the heater/motor wheel. When the pilot light is on, the heater is powered on.

#### Temperature Control and Indicator

- The controller is front-panel-adjustable. When the gelatin pan is properly in position, the temperature controller will display the heat transfer fluid temperature.

#### Interlock, Tabletop Safety

- If the table is not down and in its proper operating position, the interlock prevents the operation of the slat drive chain.

#### Interlock, Gelatin Pan Heater Safety

- The interlock on the gelatin pan turns off the power to the gelatin pan heating element if the gelatin pan is not raised into the proper operating position.

#### Interlock, Removable Panel Safety

- The interlock on the front panel stops the operation of the slat drive chain if the front panel is not in the proper operating position.

#### Chain Speed Potentiometer

- The chain speed potentiometer controls the speed, up or down, of the chain motor.

#### Wheel Speed Potentiometer

- The banding wheel potentiometer controls the speed, up or down, of the sealer motor.

# Capsule Band-Sealing Machines

## S2 Model


### Two Points of Adjustment

- The first point of adjustment is vertical, which determines how much of the banding wheels will protrude through the tabletop. The amount of wheel protruding through the tabletop will determine the amount of banding solution that will be transferred to the capsule.
- The second point of adjustment is horizontal, which determines the position of the band, with respect to the cap/body joint line.

### Banding Wheel Assembly

The banding wheels transfer gelatin from the gelatin pan to the circumference of the hard gelatin capsules.

- Wheels are a matched set, as shown by their marking on the respective parts, and must not be interchanged.
- Wheels are to be assembled and installed so that the identification markings on the banding wheels face the front of the machine.



# Capsule Band-Sealing Machines

## S2 Model

Model No.	
S2 Model	Capsule Band-Sealing Machine
Specifications	
Machine Electrical Power	230 VAC, 50/60 Hz, 4 Amps
Dimensions (mm/inches)	926mmL x 325mmW x 313mmH (mm) / 36.46" L x 12.79" W x 12.32" H (inches)
Weight (kg/lb.)	29.45kg/ 64.9lbs